

Technical data

TECHNICAL DATA INCLUDING DIMENSIONS		
Product type	Teleshake AC USB 2mm	Teleshake AC USB 3mm
Product code	7100180	7100181
Height with standard fixation pins	59.7 mm +/- 0.5 mm [2.35 in]	
Length x width	144 mm x 101 mm [5.67 x 3.98 in]	
Noise	Max. 42 dB(A)	
Protection category	IP 20	
Weight including cables	2.2 kg [4.85 lbs]	
TECHNICAL INFORMATION REGARDING SHAKING FOR ALL DEVICES		
Maximum load	1.0 kg [2.2 lbs]	
Shaker frequency (Weight reduces the max. speed)	Up to 3,000 rpm *1	Up to 2,000 rpm *1
Shaking amplitude	2 mm [0.0787 in]	3 mm [0.1181 in]
Shaking pattern	Orbital	
ENVIRONMENTAL CONDITIONS		
Tolerable relative humidity	Operation	10-80% RH (non condensing)
	Transportation and storage	10-80% RH (non condensing)
Temperature	Operation	+15°C to +32°C [+59°F to 90°F]
	Transportation and storage	-10°C to +60°C [+14°F to 140°F], non condensing

*1 The use of rpm smaller 300 with the Teleshake AC USB is possible.

